

W-WK 4/1-E Combination well HOT/COLD self cont.



10 662,00 €

hors TVA

Réf. d'article : EU500322

- Refrigerated well with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Air-curtain cooled well that can be used in a variety of ways for the best-possible energy efficiency in ongoing operation, quick reaction possibility to time-of-day based demand.
- Heating mode: Presentation area made of black glass with underlying hotplate for optimum heat transfer to your food; a matching, switchable heated cough guard is required for this mode of operation
- Pressure-foamed inner well, welded tight in a hygienic design; wrap-around hook-in rim
- Coated, circulating air fin coil evaporator with fan, low-voltage, can be folded up and rinsed
- Temperature control by means of ST501 control unit with temperature display, speed control of the fans, as well as on/off switch
- Fully-automatic defrosting; condensate drain HD 30; condensate drain required on-site
- Made of high-quality stainless steel type 1.4301
- Easiest cleaning and perfect hygiene

Temperatures COLD:

Product temperature: -1°C to +7°C (Class M2)

Air temperature: +5°C

Temperatures HOT:

Product temperature: > +65°C (in combination with thermal bridge)

Connected load: 1366 W – 230V/50Hz

Dimensions (WxDxH): 1375 x 660 x 390/655 mm

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at

Largeur:	1375
Profondeur:	660
Hauteur:	655
Version:	E
Puissance absorbée froide:	356 Watt
Ouverture de montage largeur:	1385
Ouverture de montage profondeur:	665
Cuve intérieure largeur:	1305
Cuve intérieure profondeur:	535
Cuve intérieure hauteur:	140
Puissance absorbée chaude:	1,01 kW
Voltage Volt:	230V
Fréquence Hz:	50Hz
Fluide frigorigène:	R134a
Capacité frigorifique:	600 Watt à TE -10°C
Consommation d'énergie kWh 24h:	17,7600

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at