

KGW GE-160-70-E DIAMANT Combination display case - COLD/HOT

12 950,00 €

hors TVA

Réf. d'article : EU511381

SQUARED Entirely made of stainless steel, coated evaporator, fully automatic defrosting and evaporation of condense water, ventilated cooling unit bolted to the base of the unit; Service side: Refr. part with sliding doors made of insulated glass (left), hot part with folding door made of insulated glass (right); Customer side: panorama glass pane made of safety glass. Cold part: 2 shelves made of glass adjustable in height, internal lighting on each level, incl. deep well with base trays adjustable in height. Hot part: 1 shelf, display surface able for GN 1/1 trays with a depth of 100 mm. Incl. control unit with digital temperature display. Temperature range COLD: Air 5°C / Product M2 / 3 Temperature range HOT: +65°C to +85°C Voltage: 203 V / 50 Hz, 598 Watt Dim.: (WxDxH) 1600x695x700/1375 mm

Modèle:	angulaire
Largeur:	1600
Profondeur:	695
Hauteur:	1375
Version:	E
Puissance absorbée froide:	391 Watt
Ouverture de montage largeur:	1550
Ouverture de montage profondeur:	670
Puissance absorbée chaude:	940 W
Voltage Volt:	230V
Fréquence Hz:	50Hz
Fluide frigorigène:	R134a
Capacité frigorifique:	520 Watt à TE -8°C
Consommation d'énergie kWh 24h:	5,7600

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at