

## KGW GS-127-70-Z DIAMANT Combination display case COLD/HOT: remote

**10 184,00 €**

hors TVA

**Réf. d'article : EU512385**

SLANTED Entirely made of stainless steel. Service side: Refr. part with sliding doors made of insulated glass (left), hot part with folding door made of insulated glass (right); Customer side: panorama glass pane made of safety glass. Cold part: 2 shelves made of glass adjustable in height, internal lighting on each level, incl. deep well with base trays adjustable in height. Hot part: 1 shelf, display surface able for GN 1/1 trays with a depth of 100 mm. Incl. control unit with digital temperature display. Expansion valve R 134a mounted, outlets for pipes on the bottom. Drain necessary. Temperature range COLD: Air 5°C / Product M2 / 3 Temperature range HOT: +65°C to +85°C Refrigerant: R 134a Refrigerating capacity: 400 Watt at ET -10°C Dim.: (WxDxH) 1275x695x700/1070 mm

|                                  |                    |
|----------------------------------|--------------------|
| Modèle:                          | oblique            |
| Largeur:                         | 1275               |
| Profondeur:                      | 695                |
| Hauteur:                         | 1070               |
| Version:                         | Z                  |
| Puissance absorbée froide:       | 991 Watt           |
| Ouverture de montage largeur:    | 1225               |
| Ouverture de montage profondeur: | 670                |
| Voltage Volt:                    | 230                |
| Fréquence Hz:                    | 50                 |
| Fluide frigorigène:              | R134a              |
| Capacité frigorifique:           | 520 Watt à TE -8°C |

Erreurs, changements et omissions réservés.

### IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT  
☎ +43 7612 660 61  
✉ office@ideal-ake.at

### AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT  
☎ +43 3624 211 00  
✉ office@ake.at