

Take Away BASIC GS-77-E self contained



18 667,00 €

hors TVA

Réf. d'article : EU536260

INCLINED GLASS TOP

- Minimal space concept for hot food and chilled beverages in a very small space
- Heated display case with 3 heat sources: moist heat, infrared supporting heat and primary heat – settable by means of pictogram control
- Visual and acoustic indicator of water requirement as well as easy topping up of the water tray without removing the product
- Refrigerated counter with bottle slider system; variable hook-in frames for adaptation to different bottle dimensions
- Use as display case with service or for self-service through slide-in front glass
- Glass enclosure made of tempered safety glass
- Operator side with removable and mirrored hinged doors made of one-way mirrors
- Fold-up mirror for optical multiplication of the food under the removable cutting board made of Poly-Hygiene
- Operator side with full extension drawer for easy and uncomplicated stocking
- Control unit with temperature display and pictogram control installed in the installation compartment, speed control of the fans, as well as on/off switch
- Long-lasting LED lighting per level
- Easiest cleaning and perfect hygiene
- Self-contained: With refrigerant R134a; refrigeration unit within installation compartment on the side, fully automatic condensate evaporation for self-contained model

Temperatures COLD:

Product temperature: -1°C to +7°C (Class M2)

Air temperature: +5°C

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at

Temperatures HOT:

Product temperature: > +65°C

Connected load: 2775 W - 230V/50Hz

Dimensions (WxDxH): 1175 x 865 x 1334 mm

Modèle:	oblique
Largeur:	1175
Profondeur:	1065
Hauteur:	1334
Version:	E
Puissance absorbée froide:	MEMO
Voltage Volt:	230
Fréquence Hz:	50
Fluide frigorigène:	R134a
Capacité frigorifique:	830 Watt à TE -8°C

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at