Tropical Flaps 60-70-Z Display case w. flip-up doors - remote refr.



8 525,00 €

hors TVA

Réf. d'article : EU537635



- Optimally matched self-service display case with temperature range 3M1 (air temperature +2 °C and product temperature M1: -1 °C to +5 °C)
- Display case that can be used in a variety of ways for the presentation of cold snacks on multiple levels
- No condensate formation on the soft-close removal flaps thanks to the integrated window ventilation (double air-curtain)
- Air-curtain cooling for the best-possible energy efficiency in ongoing operation, temperature control by means of a control unit with temperature display
- Inclined positioning of the intermediate shelf for first-class view of the product assortment
- Soft-close removal flaps made of tempered safety glass with integrated soft-close system for convenient food removal; optimum spit and cough protection and the best energy efficiency
- Hinged door on operator side made of insulated glass with two-way mirror
- Side windows made of insulating glass
- Transparent construction
- Long-lasting LED lighting on all levels
- Incl. price tag holder
- Easiest cleaning and perfect hygiene
- Remote refrigeration: expansion valve R134a, connection lines lead out downwards, drain required on-site for remote refrigeration

Product temperature: -1°C to +5°C (Class M1)

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Air temperature: +2°C
Connected load: 49 W – 230V/50Hz
Refrigeration capac.: 420 W at ET -8°C
Dimensions (WxDxH): 600 x710 x 700/1075 mm

Largeur:	600
Profondeur:	710
Hauteur:	960
Version:	Z
Puissance absorbée froide:	42 Watt
Ouverture de montage largeur:	580
Ouverture de montage profondeur:	670
Consommation annuelle d'énergie kWh:	1492,8500
Indice d'efficacité énergétique:	23,5169
Voltage Volt:	230
Fréquence Hz:	50
Fluide frigorigène:	R134a
Capacité frigorifique:	520 Watt à TE -8°C
Classe d'efficacité énergétique:	C
Classe de température:	M1 -1 +5
Consommation d'énergie kWh 24h:	4,0900
Classe climatique armoires réfrigérées:	3
Norme:	EN ISO 23953-2

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at