Tropical Switch Flaps 80-70-Z Switchable disp. case w. flip-up d. - remote refr.



11 879,00 €

hors TVA

Réf. d'article : EU539636



- Self-service display case with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Display case that can be used in a variety of ways for the presentation of cold or hot snacks on multiple levels
- No condensate formation on the soft-close removal flaps thanks to the integrated window ventilation (double air-curtain)
- Heating mode: With infrared supporting heat and primary heat below the black glass presentation area – settable by means of pictogram control
- Cooling mode: Air-curtain cooled display case for the best-possible energy efficiency in ongoing operation, temperature control by means of a control unit with temperature display,
- Inclined positioning of the intermediate shelf made of black glass for first-class view of the product assortment and optimum temperature transmission to the products
- Soft-close removal flaps made of tempered safety glass with integrated soft-close system for convenient food removal; optimum spit and cough protection and the best energy efficiency
- Hinged door on operator side made of insulated glass with two-way mirror
- Side windows made of insulating glass
- Transparent construction
- Long-lasting LED lighting per level
- Easiest cleaning and perfect hygiene
- Remote refrigeration: expansion valve R134a, connection lines lead out downwards, drain required on-site for remote refrigeration, control unit (250x185x175mm) and display cover (290x70mm) loose

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Temperatures COLD:
Product temperature: -1°C to +5°C (Class M1)
Air temperature: +2°C
Tempteratures HOT:
Product temperature: > +65°C

Connected load: 1250 W – 230V/50Hz
Refrigeration capac.: 480 W at ET -8°C
Dimensions (WxDxH): 800 x710 x 700/960 mm

Largeur:	800
Profondeur:	710
Hauteur:	960
Version:	Z
Ouverture de montage largeur:	580
Ouverture de montage profondeur:	670
Puissance absorbée chaude:	1,45 kW
Consommation annuelle d'énergie kWh:	1423,5000
Indice d'efficacité énergétique:	29,8656
Voltage Volt:	230
Fréquence Hz:	50
Fluide frigorigène:	R134a
Capacité frigorifique:	520 Watt à TE -8°C
Classe d'efficacité énergétique:	C
Classe de température:	H1 +1 +10
Consommation d'énergie kWh 24h:	3,9000
Classe climatique armoires réfrigérées:	3
Norme:	EN ISO 23953-2

Erreurs, changements et omissions réservés.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at