

UKW Switch 2-1-E Combination well HOT/COLD: self-contained



€ 7.338,00

excl. btw

Artikelnr.: EU500320

- Refrigerated well with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Air-curtain cooled well that can be used in a variety of ways for the best-possible energy efficiency in ongoing operation, quick reaction possibility to time-of-day based demand
- Heating mode: Presentation area made of black glass with underlying hotplate for optimum heat transfer to your food; a matching, switchable heated cough guard is required for this mode of operation
- Pressure-foamed inner well, welded tight in a hygienic design; wrap-around hook-in rim
- Coated, circulating air fin coil evaporator with fan, low-voltage, can be lifted up and rinsed
- Temperature control by means of ST501 control unit with temperature display, speed control of the fans, as well as on/off switch
- Fully-automatic defrosting; condensate drain HD 30; condensate drain required on-site!
- Made of high-quality stainless steel type 1.4301
- Easiest cleaning and perfect hygiene

Temperatures COLD:

Product temperature: -1°C to +7°C (Class M2)

Air temperature: +5°C

Temperatures HOT:

Product temperature: > +65°C (in combination with thermal bridge)

Connected load: 769 W – 230V/50Hz

DIM.: (WxDxH) 725 x 660 x 390/655 mm

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at

Breedte:	725
Diepte:	660
Hoogte:	655
Versie:	E
Opgenomen vermogen koud:	259 Watt
Inbouwopening breedte:	735
Inbouwopening diepte:	665
Binnenbak breedte:	655
Binnenbak diepte:	535
Binnenbak hoogte:	140
Opgenomen vermogen warm:	0,51 kW
Spanning Volt:	230V
Frequentie Hz:	50Hz
Koelmiddel:	R134a
Koelvermogen:	390 Watt bij VT -10°C
Energieverbruik kWh 24u:	17,7600

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
 ☎ +43 7612 660 61
 ✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
 ☎ +43 3624 211 00
 ✉ office@ake.at