

KGW GS-160-53-E DIAMANT Combination display case - COLD/HOT

€ 10.953,00

excl. btw

Artikelnr.: EU512371

SLANTED Entirely made of stainless steel, coated evaporator, fully automatic defrosting and evaporation of condense water, ventilated cooling unit bolted to the base of the unit; Service side: Refr. part with sliding doors made of insulated glass (left), hot part with folding door made of insulated glass (right); Customer side: panorama glass pane made of safety glass. Cold part: 1 shelf made of glass adjustable in height, internal lighting on each level, incl. deep well with base trays adjustable in height. Hot part: Display surface able for GN 1/1 trays with a depth of 100 mm. Incl. control unit with digital temperature display. Temperature range COLD: Air 5°C / Product M2 / 3 Temperature range HOT: +65°C to +85°C Voltage: 203 V / 50 Hz, 577 Watt Dim.: (WxDxH) 1600x695x530/1205 mm

Model:	schuin
Breedte:	1600
Diepte:	695
Hoogte:	1205
Versie:	E
Opgenomen vermogen koud:	1205 Watt
Inbouwopening breedte:	1550
Inbouwopening diepte:	670
Spanning Volt:	230
Frequentie Hz:	50
Koelmiddel:	R134a
Koelvermogen:	520 Watt bij VT -8°C
Energieverbruik kWh 24u:	4,7300

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT
☎ +43 7612 660 61
✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT
☎ +43 3624 211 00
✉ office@ake.at