

Take Away BASIC GE-77-Z remote refrigerated



€ 16.142,00

excl. btw

Artikelnr.: EU536255

SQUARED GLASS TOP

- Minimal space concept for hot food and chilled beverages in a very small space
- Heated display case with 3 heat sources: moist heat, infrared supporting heat and primary heat – setttable by means of pictogram control
- Visual and acoustic indicator of water requirement as well as easy topping up of the water tray without removing the product
- Refrigerated counter with bottle slider system; variable hook-in frames for adaptation to different bottle dimensions
- Use as display case with service or for self-service through slide-in front glass
- Glass enclosure made of tempered safety glass
- Operator side with removable and mirrored hinged doors made of one-way mirrors
- Fold-up mirror for optical multiplication of the food under the removable cutting board made of Poly-Hygiene
- Operator side with full extension drawer for easy and uncomplicated stocking
- Control unit with temperature display and pictogram control installed in the installation compartment, speed control of the fans, as well as on/off switch
- Long-lasting LED lighting per level
- Easiest cleaning and perfect hygiene
- Remote refrigeration: Expansion valve R 134a, lines lead into the installation compartment on the side, drain required on-site

Temperatures COLD:

Product temperature: -1°C to +7°C (Class M2)

Air temperature: +5°C

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at

Temperatures HOT:

Product temperature: > +65°C

Connected load: 2075 W - 230V/50Hz

Refrigeration capac.: 825 W at ET -8°C

Dimensions (WxDxH): 995 x 865 x 1334 mm

Model:	hoekig
Breedte:	995
Diepte:	1065
Hoogte:	1334
Versie:	Z
Opgenomen vermogen koud:	MEMO
Spanning Volt:	230
Frequentie Hz:	50
Koelmiddel:	R134a
Koelvermogen:	830 Watt bij VT -8°C
Energieverbruik kWh 24u:	7,5600

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at