# Tropical Flaps 60-70-E Display case w. flip-up doors - self cont.



## € 9.878,00

excl. btw

**Artikelnr.:** EU537630




- Optimally matched self-service display case with temperature range 3M1 (air temperature +2 °C and product temperature M1: -1 °C to +5 °C)
- Display case that can be used in a variety of ways for the presentation of cold snacks on multiple levels
- No condensate formation on the soft-close removal flaps thanks to the integrated window ventilation (double air-curtain)
- Air-curtain cooling for the best-possible energy efficiency in ongoing operation, temperature control by means of a control unit with temperature display
- Inclined positioning of the intermediate shelf for first-class view of the product assortment
- Soft-close removal flaps made of tempered safety glass with integrated soft-close system for convenient food removal; optimum spit and cough protection and the best energy efficiency
- Hinged door on operator side made of insulated glass with two-way mirror
- Side windows made of insulating glass
- Transparent construction
- Long-lasting LED lighting on all levels
- Incl. price tag holder
- Easiest cleaning and perfect hygiene
- Self-contained: With refrigerant R134a; fully automatic condensate evaporation for self-contained model

Product temperature: -1°C to +5°C (Class M1)

Fouten en systeemfouten gereserveerd.

**IDEAL Kältetechnik GmbH**
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Air temperature: +2°C
Connected load: 449 W – 230V/50Hz
Dimensions (WxDxH): 600 x710 x 700/1335 mm

| | |
|---|---|
| Breedte: | 600 |
| Diepte: | 710 |
| Hoogte: | 1335 |
| Versie: | E |
| Opgenomen vermogen koud: | 342 Watt |
| Inbouwopening breedte: | 580 |
| Inbouwopening diepte: | 670 |
| Jaarlijks energieverbruik kWh: | 1193,5500 |
| Energie-efficiëntie-index: | 17,1185 |
| Spanning Volt: | 230 |
| Frequentie Hz: | 50 |
| Koelmiddel: | R134a |
| Koelvermogen: | 520 Watt bij VT -8°C |
| Energie-efficiëntieklasse: | B |
| Temperatuurklasse: | M1 -1 +5 |
| Energieverbruik kWh 24u: | 3,2700 |
| Klimaatklasse Koelkasten: | 3 |
| Norm: | EN ISO 23953-2 |

Fouten en systeemfouten gereserveerd.

**IDEAL Kältetechnik GmbH**
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

**AKE Ausseer Kälte- und Edelstahltechnik GmbH**
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at