

Switch Flaps 70-Z Switchable disp. case w. flip-up d. - remote refr.



€ 9.916,00

excl. btw

Artikelnr.: EU538635

- Self-service display case with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Heating mode: With infrared supporting heat and primary heat below the black glass presentation area – settable by means of pictogram control
- Cooling mode: Air-curtain cooled display case for the best-possible energy efficiency in ongoing operation, temperature control by means of a control unit with temperature display,
- Inclined positioning of the intermediate shelf made of black glass for first-class view of the product assortment and optimum temperature transmission to the products
- Soft-close removal flaps made of tempered safety glass with integrated soft-close system for convenient food removal; optimum spit and cough protection and the best energy efficiency
- Hinged door on operator side made of insulated glass with two-way mirror
- glass build up made of tempered safety glass
- Transparent construction
- Long-lasting LED lighting per level
- Easiest cleaning and perfect hygiene
- Remote refrigeration: expansion valve R134a, connection lines lead out downwards, drain required on-site for remote refrigeration, control unit (250x185x175mm) and display cover (290x70mm) loose

Temperatures COLD:

Product temperature: -1°C to +7°C (Class M2)

Air temperature: +5°C

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at

Temperatures HOT:

Product temperature: > +65°C

Connected load: 1700 W - 230V/50Hz

Refrigeration capac.: 420 W at ET -8°C

Dimensions (WxDxH): 600 x710 x 700/960 mm

Breedte:	600
Diepte:	710
Hoogte:	960
Versie:	Z
Inbouwopening breedte:	580
Inbouwopening diepte:	670
Binnenbak breedte:	490
Binnenbak diepte:	535
Binnenbak hoogte:	75
Opgenomen vermogen warm:	1,1 kW
Spanning Volt:	230
Frequentie Hz:	50
Koelmiddel:	R134a

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH

📍 In der Schörihub 28, 4810 Gmunden, AT

☎ +43 7612 660 61

✉ office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH

📍 Pichl 66, 8984 Bad Mitterndorf, AT

☎ +43 3624 211 00

✉ office@ake.at