Tropical Switch Flaps 60-70-Z Switchable disp. case w. flip-up d. - remote refr.



€ 11.027,00

excl. btw

Artikelnr.: EU539635



- Self-service display case with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Display case that can be used in a variety of ways for the presentation of cold or hot snacks on multiple levels
- No condensate formation on the soft-close removal flaps thanks to the integrated window ventilation (double air-curtain)
- Heating mode: With infrared supporting heat and primary heat below the black glass presentation area – settable by means of pictogram control
- Cooling mode: Air-curtain cooled display case for the best-possible energy efficiency in ongoing operation, temperature control by means of a control unit with temperature display,
- Inclined positioning of the intermediate shelf made of black glass for first-class view of the product assortment and optimum temperature transmission to the products
- Soft-close removal flaps made of tempered safety glass with integrated soft-close system for convenient food removal; optimum spit and cough protection and the best energy efficiency
- Hinged door on operator side made of insulated glass with two-way mirror
- Side windows made of insulating glass
- Transparent construction
- Long-lasting LED lighting per level
- Easiest cleaning and perfect hygiene
- Remote refrigeration: expansion valve R134a, connection lines lead out downwards, drain required on-site for remote refrigeration, control unit (250x185x175mm) and display cover (290x70mm) loose

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Temperatures COLD:
Product temperature: -1°C to +5°C (Class M1)
Air temperature: +2°C
Tempteratures HOT:
Product temperature: > +65°C

Connected load: 1010 W – 230V/50Hz
Refrigeration capac.: 420 W at ET -8°C
Dimensions (WxDxH): 600 x710 x 700/960 mm

Breedte:	600
Diepte:	710
Hoogte:	960
Versie:	Z
Inbouwopening breedte:	580
Inbouwopening diepte:	670
Opgenomen vermogen warm:	1,11 kW
Jaarlijks energieverbruik kWh:	1193,5500
Energie-efficiëntie-index:	26,7208
Spanning Volt:	230
Frequentie Hz:	50
Koelmiddel:	R134a
Koelvermogen:	520 Watt bij VT -8°C
Energie-efficiëntieklasse:	C
Temperatuurklasse:	H1 +1 +10
Energieverbruik kWh 24u:	3,2700
Klimaatklasse Koelkasten:	3
Norm:	EN ISO 23953-2

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at