Tropical Switch Flaps 80-87-E Switchable disp. case w. flip-up d. - self cont.



€ 14.824,00

excl. btw

Artikelnr.: EU539931

- Self-service display case with switch function for quick switchover possibility between cold and hot operation – optimally matched to 24/7 operation
- Display case that can be used in a variety of ways for the presentation of cold or hot snacks on multiple levels
- No condensate formation on the soft-close removal flaps thanks to the integrated window ventilation (double air-curtain)
- Heating mode: With infrared supporting heat and primary heat below the black glass presentation area – settable by means of pictogram control
- Cooling mode: Air-curtain cooled display case for the best-possible energy efficiency in ongoing operation, temperature control by means of a control unit with temperature display,
- Inclined positioning of the intermediate shelf made of black glass for first-class view of the product assortment and optimum temperature transmission to the products
- Soft-close removal flaps made of tempered safety glass with integrated soft-close system for convenient food removal; optimum spit and cough protection and the best energy efficiency
- Hinged door on operator side made of insulated glass with two-way mirror
- Side windows made of insulating glass
- Transparent construction
- Long-lasting LED lighting per level
- Easiest cleaning and perfect hygiene
- Self-contained: With refrigerant R134a; fully automatic condensate evaporation for self-contained model;

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at

Temperatures COLD:
Product temperature: -1°C to +5°C (Class M1)
Air temperature: +2°C
Tempteratures HOT:
Product temperature: > +65°C

Connected load: 2060 W – 230V/50Hz
Dimensions (WxDxH): 800 x710 x 870/1505 mm

Breedte:	800
Diepte:	710
Hoogte:	1505
Versie:	E
Inbouwopening breedte:	780
Inbouwopening diepte:	670
Opgenomen vermogen warm:	2,07 kW
Spanning Volt:	230
Frequentie Hz:	50
Koelmiddel:	R134a
Koelvermogen:	590 Watt bij VT -8°C

Fouten en systeemfouten gereserveerd.

IDEAL Kältetechnik GmbH
In der Schörihub 28, 4810 Gmunden, AT
+43 7612 660 61
office@ideal-ake.at

AKE Ausseer Kälte- und Edelstahltechnik GmbH
Pichl 66, 8984 Bad Mitterndorf, AT
+43 3624 211 00
office@ake.at